

New The E-Classic range

Outdoor Wood Gasification boiler from Central Boiler



E-Classic Features & Benefits

Charge Tube

Super-heated air is injected and mixed with the hot gases from the primary firebox and starts the secondary combustion process. No catalytic device needed.

Large Reaction Chamber™

Final combustion occurs in the Reaction Chamber where extremely high temperatures aid in complete combustion. The Reaction Chamber features a large, hinged door for easy ash removal.

Power Ignition

The boiler can be fitted with an optional propane burner which allows for push-button automatic gas-fired wood ignition. This provides easy starting and automatic relighting of the fire if needed. Natural Gas conversion kit available.

EPA Hangtag

The E-Classic 3200, 2400, 2300 and 1400 are U.S. EPA Hydronic Heater Program qualified and have met the Phase 2 emissions level.

Urethane Foam Insulation

Insulation is sprayed on and forms a 100% airtight, waterproof seal around the water jacket.

Triple Insulated Firebox Door

Ergonomically designed door is lockable and features a large opening for easy loading. Door is triple insulated for maximum efficiency. Panels are powder coated for high durability. The heavy-duty door handle is durable and easy to use.

Cam Loc® Door Closure

The specially designed curved ends of the door closure fit precisely around the adjustable bearings, for a tight seal each time the door is closed.

Rear Access Panel

Designed for convenient installation and easy access to pumps and power disconnect. Up to two pumps can be installed.

FireStar™ Electronic Controller

Provides user with easy operation of the boiler with just the touch of a button. The controller automatically adjusts the primary and secondary air which optimizes the gasification process allowing the boiler to be more efficient and cleaner burning.

High Capacity Water Jacket

Provides a balance between firebox volume and water capacity for optimum performance and safety.

Insulated Chimney

Two 4-foot, insulated chimney sections are supplied. Additional sections are available for extending the chimney when needed.

Xtract™ Heat Transfer System

Transfers the heat from the exhaust to the water during the final combustion phase and before the exhaust exits the chimney.

All-Weather Steel Siding

All siding is overlapped for tighter weather seal. All panels and corners are powder coated for high durability.

Bypass Door

For redirecting exhaust when refueling.

Photo Electronic Controlled LED Lights

Long-lasting energy-efficient LED night lights save money and enhance safety. They illuminate the inside of the firebox and the front and sides of the outdoor boiler and can be conveniently set to automatically turn on at night.

Award-winning Technology, Design and Performance!

CENTRAL BOILER
E-CLASSIC
2400

- Highest Heat Output*
- Lowest Emissions*
- Over 92% Efficiency Means Less Wood
- Largest Firebox Door
- LED Lights

2010 VESTA Award - Wood Products Category

This award honors innovation in design and technology. The E-Classic 2400 was awarded the Vesta award based on features such as the eco-friendly LED lights, three-stage innovative combustion technology, FireStar electronic controller, and Power Ignition. The E-Classic 2400's award-winning performance includes its over 92% efficiency, extremely low emissions and 260,000 Btu/hr rating.



*There is no cleaner outdoor furnace
with this amount of heat output!**

*Highest Heat Output Rating and Lowest Emissions based on EPA website data, July 2, 2010.



Want to know more, get advice or order?